

# W O K R A N G E R A N G E

## 炒炉系列



### 燃气环保单头单尾炒炉（电磁安全掣）

### Gas environmental 1-ring 1-rear pot wok range

编号/Item NO.	
品牌/Brand	Elite-Flame
产品型号/Model	CS-CRE-1-G (E)
规格/Dimension	1200*1200*810+440mm
热负荷/Heat loading	42.0kW
电功率/Connected load	220V/1ph, 0.13kW
备注/Remarks	

#### 产品特点

- 炉头: 特别设置的向内火环保预混炉头, 黄铜材质, 不易变形, 耐高温腐蚀, 导热速度快
- 点火: 脉冲电子点火, 一键式操作
- 熄火保护: 离子检测熄火保护
- 设备整体框架采用SUS304不锈钢制作, 框架采用拉钉固定连接设计
- 台面整件成型、没有焊接、没有卫生死角、方便清洁
- 隔热台面, 底部设计30mm厚的玻璃棉和不锈钢封板加强台面
- 设备前臂底沿设计有挡水V型槽、面板与侧板连接处有防水胶条
- 二台设备之间的连接采用卡条连接方式, 侧臂设计有防水胶条, 防止水流入
- 设备底部用设计有不锈钢封板、起防水防虫作用
- 电磁阀控制, 火种未点燃时, 主气阀不会打开; 风机供风不正常, 供气不正常, 意外熄火等故障, 1秒钟关闭燃气, 不会出现炸锅的事故
- 新型静音风机 (220V, 50Hz, 130W), 每个炉头独立配置, 使用行链风制实现风气联动, 可调节供风大小, 体积小、风量大、噪音低
- 鼓风预混燃烧, 噪音小于65分贝, 燃烧充分, 烟气中有毒气体CO (一氧化碳) 和NOx(氮氧化物)低于一般沟风炉头  
火力强劲, 热效率高, 与一般沟风炉头相比可节能30%以上
- 炉头内冷的气体吸收炉头外壳热量, 降低炉头温度, 提高炉头的使用寿命
- 整体炉砖, 防止漏火损坏炉膛
- 感应针使用温度超过1200度, 不易烧坏
- 标配: 调料板1个、水龙头1个、锅枕1个、尾撑1个

#### Description

- Burner: Environmental gas/air pre-mix copper burner, withstand high temperature, fast thermal conductivity.
- Ignition: Electronic pulse ignition with one button operation
- Flame failure protection: ion detector flame failure protection
- Completely body with SUS304 stainless steel frame structure
- Seamless deep drawn table top without welding, hygiene and easy for cleaning
- Table top with 30mm thick of insulation material
- Front top plate edge with drip nose design to prevent water flows onto the control panel.
- Equipment are clipped together by U-channel connector
- Prevention to pests with stainless steel perforated cover board at the bottom
- Solenoid safety gas valve controller, the main gas valve doesn't open until the flame ignites. Gas supply will be cut off in 1 second once the air or gas is supplying abnormally or an unexpected flame failure appears, prevent the explosion accident
- Each burner is equipped with an innovative silent blower (220V/50Hz/130W) integrated with chain wind system self-adjusting air and gas supply
- Self pre-mixing combustion with noise level < 65dB at powerful flaming with minimal emission of carbon monoxide<0.01%.
- Energy saving >30% to compare with other blower burner
- A monolithic brick burning furnace, minimizes damaging the chamber by the strong fire
- Thermocouple withstand high temperature up to 1200 ° C, lasting long.
- Accessories:Seasoning board 1pc、Faucet 1pc、Wok stand 1pc、Rear pot 1pc

