

ROLL-IN STEAMER CABINET

车载蒸柜系列

燃气双门推车万用蒸柜(电子版控制)

Gas environmental 2-door roll-in steamer cabinet



编号/Item NO.	
品牌/Brand	Elite-Flame
产品型号/Model	SBE-2DC-G
规格/Dimension	2150*900*1900mm
热负荷/Heat loading	84.0kW
电功率/Connected load	220V/1ph, 3.0kW
备注/Remarks	

产品特点

- 6只自引射环保炉头, 热负荷84kW
- 两个主火阀门控制多个炉头, 可根据需要通过主火阀门开关选择不同蒸汽出量
- 电子点火, 一键式操作, 燃烧无需风机鼓风, 节约用电
- 设置常明火种, 配置电磁安全制, 意外熄火等故障, 1秒钟关闭燃气
- 水胆采用1.5mm耐热不锈钢加工, 4条S形火管结构, 表面隔热处理
- 设置缺水保护, 防止干烧损坏水胆
- 设置补水箱, φ1/2"全不锈钢浮球自动补水
- 专门设计的排水盒子集中蒸层排水和水胆排水, 并防止水胆水倒流入柜内和防止柜内蒸汽由下部外溢
- 设置时间控制和功率选择控制
- 可根据需要设定工作时间(0-60分钟), 时间到自动关火
- 设置超温蒸功能(电加热3kW), 加热产生过热饱和蒸汽, 柜内温度可以达130°C, 提高加热速度, 可供特殊用途使用
- 可通过温度设置保温功能(85°C), 设置柜内照明功能
- 柜体面板使用1.2mm304不锈钢, 围身0.9mm, 外表面隔热处理
- 蒸仓有效容积L×W×H=650*750*1510
- 使用18层规格推车, 每层可放置1个GN2/1盆, 标准配置2辆推车
- 特别结构的硅胶门胶边, 加上扣紧门锁, 柜门不漏蒸汽
- 硬水地区使用该设备必须装配软化水设置

Description

- 6pcs self injection environmental burner, Gas loading: 84kW
- Two control valves to control different level of steams during operation-slow, fast and holding
- One button operation with electronic ignition.
- Stand-type pilot flame and solenoid safety gas valve, cut off gas supply in 1 second when unexpected flame failure
- Water tank is made of 1.5mm stainless steel with 4 sets of S-type heating tubes that are insulated completely
- Over temperature and water lack protection. prevent dry heating
- φ1/2" stainless steel float ball valve to maintain the water volume to prevent dry heating, also with over temperature limit switch
- Special designed drainage box, integrated the cabinet and water tank drainage which can prevent over flowing into cabinet and the steam leakage from the bottom
- Smart controlling of time and temperature
- Advanced pre-setting of working time according to needs (0-60min). Optimize your working time
- Power Steaming function to generate unsaturated steam when the temperature heats up to 130 °C in chamber, thus improve the heating result special cooking
- By selecting the temperature, it can turn into a warm holding cabinet
- Chamber dimension: L×W×H=650*750*1510
- Equipped with 18 layers trolley for each steam cabinet ,each layer can be put 1 GN2/1 or 36*GN1/1
- Special silica gel sealing gaskets that prevents steam leakage when door is closed
- Recommended to install water softener before water supply inlet

